

Standard AS 568A Size O-Rings

568 -SIZE	INCHES				MILLIMETERS			
	I.D.	TOL ±	C.S.	TOL ±	I.D.	TOL ±	C.S.	TOL ±
-901	0.185	0.005	0.056	0.003	4.700	0.130	1.420	0.080
-902	0.239	0.005	0.064	0.003	6.070	0.130	1.630	0.080
-903	0.301	0.005	0.064	0.003	7.650	0.130	1.630	0.080
-904	0.351	0.005	0.072	0.003	8.920	0.130	1.830	0.080
-905	0.414	0.005	0.072	0.003	10.520	0.130	1.830	0.080
-906	0.468	0.005	0.078	0.003	11.890	0.130	1.980	0.080
-907	0.530	0.007	0.082	0.003	13.460	0.180	2.080	0.080
-908	0.644	0.009	0.087	0.003	16.360	0.230	2.210	0.080
-909	0.706	0.009	0.097	0.003	17.930	0.230	2.460	0.080
-910	0.755	0.009	0.097	0.003	19.180	0.230	2.460	0.080
-911	0.863	0.009	0.116	0.004	21.920	0.230	2.950	0.100
-912	0.924	0.009	0.116	0.004	23.470	0.230	2.950	0.100
-913	0.986	0.010	0.116	0.004	25.040	0.260	2.950	0.100
-914	1.047	0.010	0.116	0.004	26.590	0.260	2.950	0.100
-916	1.171	0.010	0.116	0.004	29.740	0.260	2.950	0.100
-918	1.355	0.012	0.116	0.004	34.420	0.300	2.950	0.100
-920	1.475	0.014	0.118	0.004	37.470	0.360	3.000	0.100
-924	1.720	0.014	0.118	0.004	43.690	0.360	3.000	0.100
-928	2.090	0.018	0.118	0.004	53.090	0.460	3.000	0.100
-932	2.337	0.018	0.118	0.004	59.360	0.460	3.000	0.100